


Digital pH Meter

DPH-2

Cat.No.4320

- **Automatic Temperature Compensation!**
- **Waterproof design!**
- **Compact & portable design!**
- **Sturdy body design for electrode-protection**
- **Electrode can be cleaned with tap water**
(Use of deionized water will damage the electrode.)





Applications

- Food and beverage production control
- Brewing, fermentation, and food process control
- Soil-based agriculture and hydroponics
- Cutting oils, alkaline washing liquids
- pH levels of fruit juices
- Quality control for aquacultures and aquariums
- pH levels of boiler liquids
- pH levels of alkaline liquid
- Other soluble solutions

**Easy
one-handed
operation**



Specifications

Measurement range : 0.0 to 14.0pH
 Resolution : 0.1pH
 Measurement accuracy : ± 0.1 pH (2.0 to 12.0pH)
 Temperature compensation range : 0 to 50°C
 (Automatic Temperature Compensation)
 Calibration : 3-points (4.0, 7.0, and 10.0)
 Power supply : watch battery (LR44)1.4Vx4
 Materials in contact with the solution :
 Main body-ABS resin/Electrode-PBT resin
 International Protection class : IP67
 Dimensions & weight : 4.5x3.0x16.3cm, 90g

All ATAGO products are designed and manufactured in Japan.

HACCP GMP GLP

ATAGO products comply with HACCP, GMP, and GLP system standards.

ATAGO CO.,LTD.

Headquarters: The Front Tower Shiba Koen, 23rd Floor
 2-6-3 Shiba-koen, Minato-ku, Tokyo 105-0011, Japan
 TEL : 81-3-3431-1943 FAX : 81-3-3431-1945
 overseas@atago.net http://www.atago.net/

ATAGO U.S.A., Inc.

TEL : 1-425-637-2107 customerservice@atago-usa.com

ATAGO INDIA Instruments Pvt. Ltd.

TEL : 91-22-2833-8038 / 8076 customerservice@atago-india.com

ATAGO (THAILAND) Co., Ltd.

TEL : 662-982-8718-9 customerservice@atago-thailand.com

ATAGO BRASIL Ltda.

TEL : 55 16 3916-6000 customerservice@atago-brasil.com

ATAGO ITALIA s.r.l.

TEL : 39 2 36557267 customerservice@atago-italia.com

ATAGO CHINA Guangzhou Co., Ltd.

TEL : 86 20-38106065 info@atago-china.com



* Specifications and appearance are subject to change without notice.